





ADVANTAGES:

- •Designed for high pressure pumps
- Exceptional anti-wear technology
- Reduces fluid friction
- Extreme thermal and oxidation stability
- Superior hydrolytic stability
- Excellent demulsibility performance
- Outstanding rust protection
- Lower filter blockage tendency

BASE OIL MEETS FOLLOWING SPECIFICATIONS:

- Denison HF-0, HF-1, HF-2
- Eaton-Vickers I-286-S and M-2950-S
- Cincinnati Machine P-68, P-69, P-70
- •US Steel 127
- •DIN 51524, Part 2
- •General Motors LH-03, LH-04, LH-06
- Sauer Danfoss
- Rexroth-Bosch
- •AFNOR E 48 603

HYDRAULIC OIL

REDUCES HAMMERING, WATER & MOISTURE, EXTENDS EQUIPMENT LIFE

ProOne Hydraulic Oil is a high performance anti-wear hydraulic oil designed to meet and exceed a wide range of hydraulic applications and requirements. It is formulated using high grade virgin mineral oils coupled with **XPL+ Technology** providing an outstanding anti-wear package.

Combined they provide outstanding protection against wear, have a high degree of purity and have excellent thermal stability for long system life.

TYPICAL PHYSICAL PROPERTIES

Characteristic	ISO 32	ISO 46	ISO 68
cSt @ 40°C (104°F)	32	46	68
cSt @ 100°C (212°F)	5.35	6.73	8.41
Viscosity Index (ASTM D-2270)	98	98	97
Flash Point, °C (ASTM D-92)	215°C (419°F)	225°C (437°F)	240°C (464°F)
Pour Point °C (ASTM D-2270)	-12°C (10.4°F)	-12°C (10.4°F)	-12°C (10.4°F)
Copper Corrosion (ASTM D-130)	1b	1b	1b
Rust Test (ASTM D-665A)	Pass	Pass	Pass

ProOne#	Description	Size	Case Pack
24005-32	Hydraulic Oil 32	5 gallon/ 18.9L Pail	1
24055-32	Hydraulic Oil 32	55 gallon/ 208L Drum	1
24275-32	Hydraulic Oil 32	275 gallon/ 1040L Tote	1

ProOne#	Description	Size	Case Pack
24005-46	Hydraulic Oil 46	5 gallon/ 18.9L Pail	1
24055-46	Hydraulic Oil 46	55 gallon/ 208L Drum	1
24275-46	Hydraulic Oil 46	275 gallon/ 1040L Tote	1

ProOne#	Description	Size	Case Pack
24005-68	Hydraulic Oil 68	5 gallon/ 18.9L Pail	1
24055-68	Hydraulic Oil 68	55 gallon/ 208L Drum	1
24275-68	Hydraulic Oil 68	275 gallon/ 1040L Tote	1